



SUBMERSIBLE CAPACITIVE TRANSMITTERS

FOR WATER LEVEL MEASUREMENTS

SERIES 46 X SERIES 46 X Ei

The Series 46 X combines the ceramic measuring cell for low pressure ranges with the μ P-electronics of the digital Series 30 pressure transmitters. The signal values of the pressure- and temperature sensors are determined by a polynomial compensation¹⁾. The values can be shown and stored on a PC and can be reprogrammed. A reference tube integrated in the cable connects the referential chamber of the sensor with the ambient pressure.

Specifications

Pressure Ranges (FS)*	30	100	300	mbar
Overpressure	300	1000	1500	mbar

* Intermediate ranges for the analog output are realizable with no surcharge by spreading the standard ranges (note that the error band will then increase proportionally)

Type	2-Wire	3-Wire
Supply (U _B) 46 X	8...28 VDC	13...28 VDC
Supply (U _B) 46 X Ei	10...30 VDC	15...30 VDC
Signal Output (scaleable)	4...20 mA	0...10 V
Load (k Ω)	<(U _B -U _{Bmin}) / 20 mA	\geq 100
Error Band typ.**	\pm 0,1 %FS	\pm 0,2 %FS
Error Band max.**	\pm 0,2 %FS	\pm 0,3 %FS

** Within the compensated temperature range

Stability	FS \geq 100 mbar: \pm 0,1 %FS	FS \leq 100 mbar: \pm 0,1 mbar
-----------	-----------------------------------	------------------------------------

Operating Temperature	0...80 °C (icing not permitted)
Compensated Range	10...50 °C

- Electrical Connection
- Reference cable PE sheath \varnothing 5,8
 - Absolute cable PUR double sheath \varnothing 4,7
 - Cable length: Standard 5 m

- Materials Contact with Media
- Housing: Stainless steel (type AISI 316L)
 - Diaphragm: Ceramic, gold plated
 - Nitrile O-ring

- Protection
- IP 68
- Weight
- \approx 400 g with 5 m cable
- Options
- Programmable, other versions

This pressure transmitter is also available as intrinsically safe version (Series 46 X Ei). It is used in explosion exposed areas, where the categories 1 and 2 are required and must only be used in combination with certified intrinsically safe equipment!



	Ex ia IIC T4		0081
PTB 06 ATEX 2011			

¹⁾ More information about the polynomial compensation and associated software you will find in the Series 41 X datasheet.

Electrical Connections

	2-Wire	3-Wire
Black	+VCC	+VCC
White	OUT/GND	GND
Red		+OUT
Blue	RS 485 A	
Yellow	RS 485 B	